

Elit (COBRA) is in great shape

- Weight: 12.5 kg (including the top and bottom camera plates)
- Reinforced aluminum 6061 T6 and carbon fiber composite
- Camera cage internal dims. in mm: 315 x 309 x 381 (H x W x D)
- 5.5 seconds boot time
- Voltage: 22-25.3 V 10.000-30.000 mah battery (6S lipo recommended) or 24 V DC power supply
- Axis working range: Tilt +90/-140, Roll +60/-760, Pan cont. 360
- Built-in voltage regulators to power external devices (camera, follow focus, wireless vision, etc.)
- IMU (gyroscope and accelerometer), 3 absolute encoders on each axis and 32-bit main processor
- Wireless controller range: 500 m
- Zoom-focus controller cable length up to 100m (CAN)

Elit (COBRA) is universal

- 3-axis hall-sensor joystick offers ultra-precise frame control
- Wide axis working range allows for seamless and steady movement
- Built-in zoom-focus controller for all Canon & Fujinon broadcast lenses
- Achieve short setup time with the toolless balancing in each axis
- Use Elit in the underslung or overslung modes without the need to change any settings
- Advanced IMU with GPS prevents horizon drift
- Lock mechanism available on the tilt and roll axis
- Hollow shafts in all axis (tilt, roll, pan) make wires routing easy
- Internal wires routing helps in operation and initial camera setup